

Specifications NXTR-PM

| | | | |
|------------------------------------------|-----------------|--------------------------------------------------------|-------------------------|
| Repeated alignment accuracy ¹ | | ±0.010 mm @6σ (Cpk ≥ 2.0) | |
| Printing accuracy ² | | ±0.020 mm @6σ (Cpk ≥ 2.0) | |
| Printing speed | | 1 to 300 mm / sec. | |
| Panel size (L x W) | Single conveyor | 48 x 48 to 610 x 610 mm | |
| | Double conveyor | Single conveyance | 48 x 48 to 610 x 510 mm |
| | | Dual conveyance | 48 x 48 to 330 x 280 mm |
| Screen frame (L x W) | | 650 x 550 mm, 29 x 29 inch, 750 x 750 mm, 750 x 810 mm | |
| Machine size (L x W x H) | | 1,280 x 1,700 x 1,480 mm | |
| Weight | | 1,600 kg | |
| Power | | 3-phase AC 200 to 230 V ±10% (50/60 Hz) | |
| Air | | 0.4 MPa | |
| Air consumption | Single conveyor | 7.7 L/min. (ANR) | |
| | Double conveyor | 37.0 L/min. (ANR) | |

*1 Under optimum Fuji conditions.

*2 Under optimum Fuji conditions. (Using CeTaQ's measurement system)