

**Safe and smart storage solutions**  
**sltower® Various 773**

Storing system for electronic components	
SMD reels	Diameter 7" – 15" / belt width 8 mm – 72 mm
SmartCarrier boxes	180 mm – 390 mm square / high 33 mm – 78 mm
Maximum reel capacity	774 reels 7" / 8 mm – 15" / 32 mm belt width
Cycle time	4 reels/min
Controlled environment	≤ 5% rF
Automated barcode processing	1D and 2D (FoV 230 x 270 mm)
Automated package registration	7" – 15" / 8 – 56 mm
Individual configurable and expandable	belt width, diameter and number units

Hardware	MASES Software
<b>S-Tower 7" – 15" / 8 mm – 72 mm</b>	<b>Material and Storing Enterprise System</b>
SPS with interchangeable memory	Component management
PC with touch panel	SQL Database
CAN-Bus technologie	Programming in .Net / C#
Automated barcode and package registration (Option)	User management
Status light (option)	Traceability management
Short way random storage	Backup management
Datalogger rH / °C (option)	Inventory monitoring
MSD-storage humidity controlled	Production scheduling
ESD conform powder coating	File Transfer Interface (ASCII data)
Terminal with safety lock (automated as option)	WebService Interface (option)
Working load 5 kg	SAP Interface (option)

Technical data and system requirement Various 773	
Dimension (W x D x H)	1467 mm x 1584 mm x 2600 mm
Weight (without cassettes)	450 kg
Power supply	200 – 230 V / 50 – 60 Hz / 250 W
Network	Ethernet / LAN
DryFlow-Unit sensor controlled	≤ 5% rF / 250 – 2000 W
Basic PC for MASES Master Software	Win 10 Pro / USB Ethernet / LAN

The content is subject to change without notice due to constant product development.

The information is current as of 2015.

©2015 FUJI EUROPE CORPORATION GmbH. All Rights Reserved.