

**Create the future
NXTR PM**

■ Specifications

		NXTR PM	NXTR PM with PM Smart Changer ^{1,2}
Repeated alignment accuracy ^{*3}		±0.010 mm Cpk ≥ 2.0 (6σ)	
Printing accuracy ^{*3}		±0.020 mm Cpk ≥ 2.0 (6σ)	
Printing speed		1 to 300 mm/sec	
Panel size (L x W)	Single conveyer	48 x 48 mm to 610 x 610 mm	
	Double conveyer	Single conveyance	48 x 48 mm to 610 x 510 mm
		Dual conveyance	48 x 48 mm to 330 x 280 mm
Screen frame (L x W)		650 x 550 mm, 29 x 29 inch, 750 x 750 mm, 750 x 810 mm	29 x 29 inch, 750 x 750 mm
Backup block size		380 mm, 480 mm, 560 mm, 620 mm	48 x 38 mm to 330 x 270 mm
PM Smart Changer rack levels		-	4 levels
Weight		1,600 kg	1,800 kg
Power		3-phase AC 200 to 230 V ±10 V (50/60 Hz)	
Air		0.4 MPa	

*1 Option

*2 When changing backup blocks automatically, backup blocks, backup exchange frames, and adapters that support PM Smart Changer are required.

*3 Under optimum Fuji conditions.

The content is subject to change without notice due to constant product development.

The information is current as of January 2022.

©2022 FUJI CORPORATION. All Rights Reserved.