

Create the future NXTR-A

Specifications NXTR A model

Module			1R module		2R module		
Panel size (L x W)	Single conveyor		48 x 48 to 750 x 610 mm		48 x 48 to 370 x 610 mm		
	Double conveyor	Single conveyance	48 x 48 to 750 x 510 mm		48 x 48 to 370 x 510 mm		
		Dual conveyance	48 x 48 to 750 x 280 mm		48 x 48 to 370 x 280 mm		
Weight	Double conveyor		680 kg		800 kg		
Base			One module base		Two module base		
Air consumption			70 L/min (ANR)		140 L/min (ANR)		
Weight ^{*1}			480 kg		910 kg		
Head			RH28	RH20	RH08	RH02	RH01
Throughput ^{*2}	Productivity priority mode		55,000 cph	50,000 cph	30,000 cph	9,000 cph	6,000 cph
			60,000 cph	55,000 cph	-	-	-
Placing accuracy ^{*2}			±0.025 mm Cpk ≥ 1.00				
	Heightened accuracy mode		±0.015 mm 3σ		-		
Power			3-phase AC 200 to 230 V ±10 V (50/60 Hz)				
Air			0.4 MPa				

^{*1} The two module base dedicated for 1R modules is 890 kg.
^{*2} Under optimum Fuji conditions.

The content is subject to change without notice due to constant product development.
The information is current as of April 2023.
©2023 FUJI CORPORATION. All Rights Reserved.