

**Create the future
NXTR-A**

Specifications NXTR A model

| Module | | 1R module | | | 2R module | | |
|--------------------------------|----------------------------|--|-------------------------|------------|-------------------------|-------------------------|--|
| Panel size (L x W) | Single conveyor | 48 x 48 to 750 x 610 mm | | | 48 x 48 to 370 x 610 mm | | |
| | Double conveyor | Single conveyance | 48 x 48 to 750 x 510 mm | | | 48 x 48 to 370 x 510 mm | |
| | | Dual conveyance | 48 x 48 to 750 x 280 mm | | | 48 x 48 to 370 x 280 mm | |
| Weight | Double conveyor | 680 kg | | | 800 kg | | |
| Base | | One module base | | | Two module base | | |
| Air consumption | | 70 L/min (ANR) | | | 140 L/min (ANR) | | |
| Weight ^{*1} | | 480 kg | | | 910 kg | | |
| Head | | RH28 | RH20 | RH08 | RH02 | RH01 | |
| Throughput ^{*2} | | 55,000 cph | 50,000 cph | 30,000 cph | 9,000 cph | 6,000 cph | |
| | Productivity priority mode | 60,000 cph | 55,000 cph | - | - | - | |
| Placing accuracy ^{*2} | | ±0.025 mm Cpk ≥ 1.00 | | | | | |
| | Heightened accuracy mode | ±0.015 mm 3σ | | | - | | |
| Power | | 3-phase AC 200 to 230 V ±10 V (50/60 Hz) | | | | | |
| Air | | 0.4 MPa | | | | | |

^{*1} The two module base dedicated for 1R modules is 890 kg.
^{*2} Under optimum Fuji conditions.

The content is subject to change without notice due to constant product development.
 The information is current as of April 2023.
 ©2023 FUJI CORPORATION. All Rights Reserved.