

**Create the future
NXTR-S**

Specifications NXTR S model

Module		1R module		2RV module		2R module		
Panel size (L x W)	Single conveyor	48 x 48 to 750 x 610 mm		48 x 48 to 370 x 610 mm				
	Double conveyor	Single conveyance	48 x 48 to 750 x 510 mm		48 x 48 to 370 x 510 mm			
		Dual conveyance	48 x 48 to 750 x 280 mm		48 x 48 to 370 x 280 mm			
Weight	Double conveyor	610 kg		640 kg		730 kg		
Base		One module base				Two module base		
Air consumption		50 L/min (ANR)				100 L/min (ANR)		
Weight ^{*1}		430 kg				800 kg		
Head		RH28	RH20	RH08	RH02	RH01		
Throughput ^{*2}	2RV module with MFU-63		55,000 cph	46,000 cph	27,000 cph	-	-	
		Productivity priority mode	60,000 cph	50,000 cph	-	-	-	
	1R/2R module with MFU-63		52,000 cph	46,000 cph	27,000 cph	8,000 cph	5,200 cph	
Productivity priority mode		57,000 cph	50,000 cph	-	-	-		
Placing accuracy ^{*2}		±0.025 mm Cpk ≥ 1.00						
	Heightened accuracy mode	±0.015 mm 3σ						
Power		3-phase AC 200 to 230 V ±10 V (50/60 Hz)						
Air		0.4 MPa						

^{*1} The two module base dedicated for 1R modules is 780 kg.

^{*2} Under optimum Fuji conditions.

The content is subject to change without notice due to constant product development.

The information is current as of April 2023.

©2023 FUJI CORPORATION. All Rights Reserved.