

## Create the future NXTR-S

### Specifications NXTR S model

Module		1R module		2RV module		2R module						
Panel size (L x W)	Single conveyor	48 x 48 to 750 x 610 mm		48 x 48 to 370 x 610 mm								
	Double conveyor	Single conveyance	48 x 48 to 750 x 510 mm	48 x 48 to 370 x 510 mm								
		Dual conveyance	48 x 48 to 750 x 280 mm	48 x 48 to 370 x 280 mm								
Weight	Double conveyor	610 kg		640 kg		730 kg						
Base		One module base				Two module base						
Air consumption		50 L/min (ANR)				100 L/min (ANR)						
Weight <sup>*1</sup>		430 kg				800 kg						
Head		RH28		RH20		RH08		RH02		RH01		
Throughput <sup>*2</sup>	2RV module with MFU-63		55,000 cph		46,000 cph		27,000 cph		-		-	
	Productivity priority mode		60,000 cph		50,000 cph		-		-		-	
	1R/2R module with MFU-63		52,000 cph		46,000 cph		27,000 cph		8,000 cph		5,200 cph	
	Productivity priority mode		57,000 cph		50,000 cph		-		-		-	
Placing accuracy <sup>*2</sup>		Heightened accuracy mode		±0.015 mm 3σ		±0.025 mm Cpk ≥ 1.00		-				
Power		3-phase AC 200 to 230 V ±10 V (50/60 Hz)										
Air		0.4 MPa										

<sup>\*1</sup> The two module base dedicated for 1R modules is 780 kg.

<sup>\*2</sup> Under optimum Fuji conditions.

The content is subject to change without notice due to constant product development.

The information is current as of April 2023.

©2023 FUJI CORPORATION. All Rights Reserved.