

Extreme flexibility and limitless expandability sFAB-D

Specifications			
Panel size (L x W)	Single conveyor	48 x 48 mm to 600 x 435 mm ^{*1}	
Panel thickness	Single conveyor	0.4 to 8.0 mm	
Supported parts		Radial parts, Axial parts and DIP/odd-form parts	
Head	sH02	sH08	sOF
Part size	1608 (0603") to 200 x 200 mm ^{*2}	1608 (0603") to 24 x 24 mm (diagonal 33.9 mm)	1608 (0603") to 52 x 52 mm (180 x 52 mm)
Part height	75 mm	20 mm ^{*3}	65 mm
Part weight	700 g	50 g	600 g
Thoroutput ^{*4}	3,850 cph	6,000 cph	2,400 cph
Machine size (L x W x H)	1,000 x 2,450 x 1,665 mm		
Weight	1,700 kg		
Power	3-phase AC200 to 230 V ±10% (50/60 Hz)		
Air	0.5 MPa		
Air consumption	50 L/min (ANR)		

*1 When using shift conveyance.
 *2 Contact your Fuji representative in advance.
 *3 The part height includes the leads.
 *4 Under optimum Fuji conditions.

The content is subject to change without notice due to constant product development.
 The information is current as of May 2026.
 ©2026 FUJI CORPORATION. All Rights Reserved.